

USE AND INSTRUCTIONS

Thank you for purchasing a SIRIUS SIGNAL product. Please read all instructions before you use it. Your SIRIUS SIGNAL LED VDS device will give you years of trouble-free service if you follow these simple instructions:

OPERATION OF THE DEVICE:

- To turn on, hold the device body in one hand and turn optical lens clockwise until the light turns on.
- To turn off, turn the lens optic counterclockwise and continue to turn it one full turn after the light goes off. This prevents the light from coming on accidentally.

CAUTION: do not look directly into the optic when it is operating; do not shine into the eyes of others. Eye damage can occur! This device is for emergency use only!

IMPORTANT:

Check for continuity of the O-RING/ seal by a visual check through the clear lower portion of the Optical lens cap. A solid continuous black ring indicates a proper seal. Occasionally clean and lightly lubricate your O-RING and cap threads. USE ONLY SILICONE GREASE, NEVER USE AEROSOL SPRAY LUBRICANTS

IF YOUR SOS DISTRESS SIGNAL FLOODS

- Remove and discard batteries
- Flush body and all parts with warm fresh water; preferable distilled water. DO NOT USE SALT WATER.
- Dry thoroughly then check for damage or corrosion.
- Return to factory or replace parts as necessary (LED is only replaceable as unit)

BATTERIES

Install only positive (+) end up towards optical lens cap. Use alkaline cells for best results.

CAUTION: Battery formulations can emit hydrogen gas. This gas can create an explosion potential in sealed devices if it is not vented or removed. The platinum catalysts included in our devices help remove this gas.

Do not insert batteries into VDS if electrical components are damaged or missing. Do not insert batteries backwards or other than positive + end up. Do not mix batteries of different types or state of charge; always use fresh batteries of same type.

IMPORTANT

Remove batteries from the device during long periods of storage. Remove exhausted, leaking or flooded batteries from the device immediately and DO NOT REUSE THEM, LEAKING BATTERIES CAN BE CORROSIVE OR CAUSE SKIN IRRITATION. Improper installation of the batteries may damage your LED VDS and void the warranty. FOLLOW BATTERY MANUFACTURER'S SUPPLIED SHELF LIFE GUIDELINES and EXPIRATION DATE ON BATTERY. Sirius Signal recommends checking and replacing batteries at the start of each season. For extended use carry spare batteries for additional run time.